

SealCraft by Contour Windows - Product Line Summary

1000 Series

Project Out and Casement

AAMA AW PG70 rated

Historic and non-historic profile frame available

1" insulated Glass – Thermal break construction – 2.5" Frame - .125 Nominal wall thickness

Highly engineered product series can be produced in many configurations.

2000 Series

Single Hung – Horizontal Slider – Fixed – Historic Fixed

AAMA AW PG70 – PG90 rated

Blast Mitigation – Impact Resistant – Florida Product approval (SH only)

1" insulated Glass – Thermal break construction – 3.25" Frame - .078 Nominal wall thickness

4000 Series

Single Hung – Horizontal Slider – Fixed – HS or FX over Louver

AAMA CW PG50 rated

Impact Resistant - Florida Product approval (HS & FX)

5/8" insulated Glass – Thermal break construction – 2.5" Frame - .062 Nominal wall thickness

8000 Series

Double Hung Historic and Non-Historic

AAMA CW PG50 rated

7/8" insulated Glass – Thermal break construction – 3.25" Frame - .062 Nominal wall thickness

Versatile design with numerous options for various applications.

Accessories

Wide variety of systems including Subframes and Panning in Historic and Non-Historic frames

Numerous trims, flanges, flashings and mullions.

